GROWMORE



= World Headquarters

MATERIAL SAFETY DATA SHEET M.S.D.S.

1- PRODUCT IDENTIFICATION

TRADE NAME (as labeled)

: SEA GROW - 4 -26-26

MANUFACTURER'S NAME

GROW MORE, INC. 15600 New Century Drive

Gardena, CA 90248 Tel. (310) 515-1700 Fax (310) 515-4937

DATE PREPARED/REVISED

March 20, 2000

NAME OF PREPARER

H. Langheim

II - HAZARDOUS INGREDIENTS

Exposure Limits in Air (give units)

Chemical Name

Copper EDTA

Zinc EDTA

CAS No. & %

ACGH TLV

OSHA PEL OTHER (specify)

Sodium Molybdate Manganese EDTA 7439987 7439965

7440508

7440666

5 mg/m3

5 mg/m3

Oral LD50Rat: 1750 mg/kg

..

III- PHYSICAL PROPERTIES

VAPOR DENSITY (AIR = 1)

: N/A

SPECIFIC GRAVITY

: Approx. 1.7 g/cc

SOLUBILITY IN WATER

: 300 g/1 or greater

VAPOR PRESSURE, mmHg AT 20°C

: N/A

APPEARANCE AND ODOR

: Fine crystals & powder

MELTING POINT OR RANGE, °F

: Not established

BOILING POINT OR RANGE, °F 3

: N/A

EVAPORATION RATE (BUTYLACETATE = 1)

: 0

DECOMPOSITION TEMPERATURE:

: 250 – 374°F

pH 1% SOLUTION

: 4.5 -- 5.5

MOLECULAR WEIGHT

: 110 - 117

| MSDS for Sea Grow – 4-26-26 (continuation) | | Page No. 2 |
|--|--|-------------------|
| CHEMICAL NAME | : Proprietary mixture containing Ammonium Pho Potassium Phosphate, Potassium Nitrate, Potas Ammonium Sulfate, Ammonium Nitrate, Urea Micronutrients | sium Sulfate, |
| IV – FIRE AND EXPLOSION | | |
| FLASH POINT. °F (Give Method) AUTO IGNITION TEMPERATURE °F FLAMMABLE LIMITS IN AIR (Vol.%) | | |
| FIRE EXTINGUISHING MATERIALS water spray foam | carbon dioxide dry chemical | other |
| SPECIAL FIREFIGHTING PROCEDUR | E: Use abundant amount of water in early stages of | fire. |
| | ARDS: When large quantities are involved in fire, so n Oxides. In such conditions application of water m | |
| V – HEALTH HAZARD INFORMATI | ON | |
| L.D. 50 | : Not established. | |
| SYMPTOMS OF OVEREXPOSURE FO | R EACH POTENTIAL ROUTE OF EXPOSURE: | |
| INHALED | : Dust can irritate upper respiratory syst | em. |
| CONTACT WITH SKIN OR EY | YES: Prolonged skin contact may cause Der irritate eyes. | matitis. Dust may |
| ABSORBED THROUGH SKIN | : Not known adverse effects at this time |) <u>.</u> |
| SWALLOWED | : Nausea, diarrhea, diuresis, muscular d | ebility. |
| FIRST AID (EMERGENCY) PRODEDU | URES: | |
| | Wash thoroughly with water for at least 15 minutes. Hold eyelids apart during flushing. Send patient immediately to physician. | |
| SKIN CONTACT : Was | sh with soap and water. | |
| INHALED : Ren | nove from exposure. Treat symptomatically. | |
| Do | Rinse mouth. Drink 2-3 glasses of water and seek medical assistance. Do not induce vomiting or give anything by mouth to an unconscious person. | |

| MSDS for Sea Grow – 4-26-26 (continuation) | Page -3- |
|---|-----------------------|
| SUSPECTED CANCER AGENT? _X_No This product's ingredients are not found in the list below. | |
| Yes FEDERAL OSHA NTP IARC | · |
| (California employers using CAL-OSHA regulated carcinogens must regist CAL-OSHA and Federal OSHA carcinogen lists are similar). | ter with CAL-OSHA, Th |
| VI – REACTIVITY DATA | · |
| STABILITY : X Stable Unstable | |
| CONDITIONS TO AVOID: Heating with Sodium Phosphite; dissolving with long exposure to tin, solder, tin plate or stagnate | |
| INCOMPATIBILITY Material to avoid) : Corrosive to Aluminum, Steel, Brass, Copper. | |
| HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION I Oxides. | PRODUCTS): Nitrogen |
| HAZARDOUS POLYMERIZATION: May occurX W | fill not occur |
| CONDITIONS TO AVOID : Avoid fire. | |
| VII – SPILL, LEAK & DISPOSAL PROCEDURES: | |
| SPILL RESPONSE PROCEDURE (Include employee protection measures): | |
| Sweep into breaker. Dilute with sufficient water. Add soda ash. Mix and neutrorian into the sewer with abundant water. | ralize with 6m HCL. |
| PREPARINNG WASTES FOR DISPOSAL, (Container types, neutralization, etc.): | |
| Remove slowly into a large container of water. Add soda ash, slightly stirring, siphon into another container. Neutralize with 6in HCL and drain into the sewer | |
| | |
| | • |